

---

Subject: : QT

Topic: : QSqlDatabase: QSQLITE driver not loaded

Re: QSqlDatabase: QSQLITE driver not loaded

Author: : BSzili

Date: : 2015/1/23 13:44:23

URL:

Before creating a qmake project, I added

Quote:

```
-Wl,-rpath-link,/sobjs -L/sobjs
```

to the link flags in my Makefiles, and the warnings above went away. I still don't have any SQL drivers, so these warnings aren't seem to be related.

Is there any way to monitor where Qt tries to load its SQL plugins from?

edit: I fired up snoopy to see what's going on. This is what I get when Qt tries to open the SQL plugins:

Quote:

```
00621 : brewtarget : FAIL = Lock("/qt/home/.config/Trolltech.conf",SHARED) [55uS]
00622 : brewtarget : FAIL = Lock("/qt/home/.config/Trolltech.conf",SHARED) [26uS]
00623 : brewtarget : FAIL = Lock("/qt/home/.config/Trolltech.conf",SHARED) [32uS]
00624 : brewtarget : FAIL = Lock("/qt/home/.config/Trolltech.conf",SHARED) [26uS]
00625 : brewtarget : FAIL = Lock("/qt/home/.config/Trolltech.conf",SHARED) [30uS]
00626 : brewtarget : FAIL = Lock("/qt/home/.config/Trolltech.conf",SHARED) [26uS]
00627 : brewtarget : FAIL = Lock("/sqldrivers/.",SHARED) [35uS]
00628 : brewtarget : FAIL = Lock("/sqldrivers/.",SHARED) [24uS]
```